

TECHNICAL DATA SHEET

DISPERSION FOR LATEX APPLICATIONS



TUBALL™ LATEX H₂O is a suspension based on TUBALL™ single wall carbon nanotubes produced by OCSiAl. TUBALL™ LATEX H₂O suspensions are available in several versions, with various surfactants. TUBALL™ single wall carbon nanotubes are a unique additive that provides electrical conductivity at low dosages not achievable with any standard conductive additive. These low dosages enable reductions in the electrical resistivity of the material with minimal impact on the host matrix, including retaining and even improving mechanical properties, minimally increasing density, and limiting the influence on the rheological properties and color.

TUBALL™ LATEX H₂O 0.5 % is a suspension specifically designed to provide electrical conductivity for different types of latex articles. Improvements in properties such as modulus and tensile strength can be achieved, while elongation at break can be retained.

Note: For more information about the dosage and mixing conditions of TUBALL™ LATEX H₂O, see the processing guidelines.

Before use, ensure that the suspension is stirred vigorously.

Adjust the pH of the suspension to be equal to or higher than the pH of the latex in which it will be used.

Dispersion composition

TUBALL™ single wall carbon nanotubes	0.5 %
Water	97 %
Sodium salt of polynaphthalene sulphonic acid	2.5 %

Typical properties

Appearance	Black colored liquid
pH	8.3 –10.5
Optical absorption*, 500 nm	≥ 0.45
Density	~1 g/cm ³

* Measurements at a concentration of 0.001 wt. % and an optical length of 10 mm.

Packaging

Plastic cans (1, 3, 5, 10, 20 liters). OCSiAl provides TUBALL™ LATEX H₂O test samples in plastic cans (1 liter) upon signing of the Material Transfer Agreement, whereby the recipient agrees to disclose test results to OCSiAl.

Storage and transportation

The product is stable in its unopened original packaging when stored at a temperature conditions + 5 to + 50 °C. The recommended storage life is up to 9 months when stored as directed.

Once opened container should be tightly closed until the product used. The recommended storage time of opened containers is 72 hours.

Safety

To ensure safe handling, the appropriate safety regulations should be observed. OCSiAl recommends that every user should be able to apply the safe handling procedures necessary for the user's applications before any handling or manufacturing takes place. A Material Safety Data Sheet outlining the hazards and handling methods for TUBALL™ LATEX H₂O is available.

Warranties and disclaimer

The Products correspond to the chemical composition indicated in the Technical Data Sheet and the Material Safety Data Sheet supplied with the Product. The information contained in this document (Information) is based on trials carried out by OCSiAl and may contain inaccuracies or errors that could cause injury, loss or damage.

OCSiAl gives no further warranty and makes no further representation regarding the Products and/or the accuracy of Information and/or suggestions for any particular use of the Products or Information, or that suggested use will not infringe any patent. The Products and Information are supplied on an "as is" basis. These express provisions are in place for all warranties, representations, conditions, terms, undertakings and obligations implied by statute, common law, custom, trade usage, course of dealing or otherwise (including implied undertakings of satisfactory quality, conformity with description, fitness for purpose and reasonable skill and care), all of which are hereby excluded to the maximum extent permitted by applicable law.

Place of production

Shenyang, China

CONTACT INFORMATION

ASIA	EUROPE	NORTH & SOUTH AMERICA	
<p>KOREA Office 208, Pilot Plant Bldg. 12, Gaetbeol-ro, Yeonsu-gu, Incheon 406-840 Republic of Korea +82 50 8113 6959 asiapacific@ocsial.com</p> <p>HONG KONG Room 1102, 11/F, Lippo Sun Plaza, 28 Canton Road, Tsim Sha Tsui, Kowloon, Hong Kong +852 21627385</p> <p>JAPAN Kusumoto Chemicals Ltd. Kusumoto Bldg. 1-11-13 Uchikanda Chiyoda-ku, Tokyo, Japan, 1010047 +81 03 32928685 info_tuball@kusumoto.co.jp</p>	<p>CHINA #2004, 20th Floor, Block B, Dachong Business Centre, No. 9678, Shennan Road, Nanshan District, Shenzhen, Guangdong, China +86 135 90125295</p> <p>Room B8, Naked Hub, Building 1, No. 818, Shenchang Road, Minhang District, Shanghai, China china@ocsial.com</p>	<p>LUXEMBOURG 1 Rue de la Poudrerie L-3364 LEUDELANGE Grand-Duche de Luxembourg +352 27990373 europe@ocsial.com</p> <p>ISRAEL Nemo Nano-Materials Ltd. 7th Hatnufa Str. (Kodak building), Petach Tinkva, P.O 3147 4951025, Israel +972 525452481 israel@ocsial.com</p> <p>RUSSIA 29, bld. 2, Kalanchevskaya Str., Moscow, 107078 +7 499 653 5152</p> <p>24, Inzhenernaya Str., Novosibirsk 630090, Russia +7 383 201 8387 russia@ocsial.com</p>	<p>USA 500 S Front Str., Suite 860, Columbus, OH 43215 +1 415 906 5271 usa@ocsial.com</p>